

XRM 2250
Part No. XRM225032X32CAFFF000
Modular Hot-Swap Matrix Switching System



General Description:

The **XRM225032X32CAFFF000** is a matrix switch and switching subsystem that provides a complete 32x32 matrix, including hot-swappable cards, redundant power supplies, and system controller in a 6 RU chassis. The modularity of the XRM225032X32CAFFF000 permits a wide variety of configurations ranging from 32x32 up to 512x512. The unit provides easy access to cards for seamless upgrades and maintenance via the front panel without requiring cables to be disconnected or disrupting the signal paths of other cards in the system.

Specifications:

Operating Frequency:	950-2150 MHz
Configurations:	32x32 up to 512x512 (32x32 in 6 RU)
Impedance:	75
Insertion Loss:	0 ± 2 dB
Frequency Response:	± 3 dB
Isolation:	
<input-to-input>):</input-to-input>	60 dB typical
<input-to-output):< td=""><td>60 dB typical</td></input-to-output):<>	60 dB typical
<input-to-output, different="" input):<="" td=""><td>50 dB typical</td></input-to-output,>	50 dB typical
Input P1dB:	0 dBm
Normal Operating Input Power Level:	-50 dBm to -10 dBm
Noise Figure:	16 dB max.
Return Loss:	>13 dB
RF Connectors:	Type "F", 75 T
Power Requirements:	90 to 264 VAC, 47 to 63 Hz
Power Consumption:	150 W
Local Control:	Front panel keypad with LCD display
PC Remote Control:	RS-232, RS-422/485, SNMP, TELNET or TCP/IP via customer-supplied PC
Software:	Basic PC-compatible operating software and system protocol included with system
Mechanical:	6 RU (10.5" H x 19" W x 20" D)
Weight:	60.5 lbs.



250 Airport Road • Indiana, PA 15701 • (800) 839-3658 • (724) 349-1412 • Fax: (724) 349-1421

<http://www.gecinc.com/> • info@gecinc.com



250 Airport Road • Indiana, PA 15701 • (800) 839-3658 • (724) 349-1412 • Fax: (724) 349-1421

<http://www.gecinc.com/> • info@gecinc.com

© 2005 Quitech Electronics and Communications Inc. All rights reserved. All product designs and specifications are subject to change without notice.
XRM225032X32CAFF000 Rev D