

**LS4 2150A**  
**LS042150A1FVA000**  
**4-Way Active Splitter (950-2150 MHz)**

**General Description:**

The **LS042150A1FVA000** is a commercial quality 4-way splitter that meets strict level and match specifications achieved through the use of Quintech's proprietary microstrip and SMT technology. It operates over the 950-2150 MHz frequency range and permits signal splitting with zero loss, eliminating the need for external distribution amplifiers. LNB DC power insertion that can be switched on or off via the front panel mounted slide switch (see LNB Power specification below).

Note: All unused RF output ports must have 75  $\Omega$  terminations.

**Specifications:**

<b>Frequency:</b>	950-2150 MHz
<b>Impedance:</b>	75 $\Omega$
<b>P1dB:</b>	+3 dBm
<b>OIP<sup>3</sup>:</b>	+17.5 dBm
<b>Insertion Loss:</b>	0 $\pm$ 2 dB
<b>Frequency Response:</b>	$\pm$ 1 dB
<b>Isolation:</b>	18 dB
<b>Input Return Loss:</b>	14 dB
<b>Output Return Loss:</b>	15 dB
<b>Noise Figure:</b>	9 dB
<b>RF Connectors:</b>	Type F, 75 $\Omega$
<b>Power Requirements:</b>	18-24 V <sub>DC</sub> , @ 1.0A via 2-pin quick connect barrier strip
<b>LNB Power:</b>	18 V <sub>DC</sub> , 850 mA max. available for LNB power
<b>Power Consumption:</b>	6 W, plus customer LNB power load
<b>Mechanical:</b>	1 RU (1.75" H x 19" W x 6.5" D)
<b>Weight:</b>	4.5 lbs. gross (boxed), 2.0 lbs. net
<b>Certifications:</b>	CE, NRTL / TUV, FCC Part 15



250 Airport Road • Indiana, PA 15701 • (800) 839-3658 • (724) 349-1412 • Fax: (724) 349-1421

<http://www.quintechelectronics.com/> • [info@quintechelectronics.com](mailto:info@quintechelectronics.com)