

XTREME 32-C

32 Port Fan-In L-Band RF Matrix Switch

QF12200V16X16CS3AA1000

16x16 SMA(f)

Exclusive Flexible Matrix Architecture, Industry Leading Specifications, and Hot-Swappable Components Provide an *XTREME* Signal Management Solution

The ***XTREME 32-C*** L-Band matrix switch is a full fan-in (combining) non-blocking signal management solution that combines one or more inputs to an output. The design features an industry exclusive architecture that supports both symmetric and asymmetric configurations of 32 combined inputs and outputs in a compact 1 RU chassis. Hot-Swappable redundant power supplies, I/O Modules, and a field replaceable cooling fan provide maximum reliability.

950-2450 MHz Operating Range

Flexible Matrix Configurations up to (16x16, 28x4, 24x8)

Redundant Hot Swappable Power Supplies

Field Replaceable Cooling Fan

Hot-swappable Input and Output Adapters

Adjustable Input and Output Gain

Dual Gigabit Ethernet Ports



**Convenient Local Control and
Status Monitoring**

**Field Replaceable
Cooling Fan**

**Hot Swappable I/O
Adapters**

**Independent Input and
Output gain control
to balance levels and cable loss**

**Dual Gigabit Ethernet Ports
Remotely controllable via secure web
browser interface, SNMP, TCP, API, or
TELNET**



**SMA, BNC 50, BNC 75, and mixed
connector configurations available.**

**Hot-swap
Redundant Power Supplies**

250 Airport Road • Indiana, PA 15701 • (800) 839-3658 • (724) 349-1412 • Fax: (724) 349-1421

<http://www.quintechelectronics.com/> • info@quintechelectronics.com

© 2023 Quintech Electronics and Communications Inc. All rights reserved. All product designs and specifications are subject to change without notice
QF12200V16X16CS3AA1000 Rev J, CO# 32249 (Page 1 of 2)



32 Port Fan-In L-Band RF Matrix Switch

Specifications and Operating Conditions

As Configured/Expandable to:	16x16	
RF Connectors:	SMA(f)	
Operating Frequency:	950-2150 MHz	850-2450MHz
Frequency Response: Default Gain: typically Centered @ 0 dB	+/- 2 dB	+/- 3dB
Flatness over any 36MHz:	+/- .5 dB	+/- .7 dB
Input P1dB:		
Default Gain:	0 dBm min	
Max Input Gain:	-15 dBm typical*	
Max RF Output Power:	>11 dBm	
Noise Figure:		
Default Gain:	13 dB max (26 dB Full Fan-In)	14 dB max (26 dB Full Fan-In)
Max Input Gain:	6 dB typical * (21 dB Full Fan-In)*	7 dB typical * (21 dB Full Fan-In)*
OIP3:		
Default Gain:	10 dBm min	8 dBm min
Input Return Loss:	14 dB min	14 dB min
Output Return Loss:	14 dB min	14 dB min
Isolation:		
Input to Input:	60 dB min	
Output to Output:	60 dB min	
Input to Output:	55 dB min	50 dB min
Input Gain Range:	-14.5 to 17 dB in .5 dB steps	
Output Gain Range:	-18.5 to 13 dB in .5 dB steps	
RF Sensing Range:	-50 to 0 dBm	
Output AGC Tracking Range:	-50 to -10 dBm setpoint	
Switching Speed:	150 mS per cross point typical	
	<2 uS from break to make	
Maximum Input Power: (No Damage)	20 dBm (30 VDC max on any port)	

Control:	
Local Control:	
Front Panel 2.2" LCD Display with Rotary Knob	
Remote Control:	
Dual 10/100/1000 Base Tx Ethernet Ports	
SNMP	v2c, v3
TCP/IP	Quintech 2.15 Protocol (Port 9100)
Web Server	
Secure Web Server with Custom SSL Certificate	
TELNET with option to disable	
Macro Scripting Language to Automate Changes and Monitoring	
XR Bus Expansion Standard	
Optional Ethernet Expansion	
NTP Time Client	

Alarms and Logging:	
SNMP Traps on Status Change	
SNMP Trap on Crosspoint Change	
SysLog, SQL, or CSV Format Log File	

Power and Cooling Requirements:	
AC Input Range:	100-240 VAC Autoranging 50/60 Hz 5A max
Hot-Swappable Redundant Supplies with Separate AC Inlets	
Power Consumption:	100 W typical
Fan:	Long-life ball bearing fan (field swappable)
Input and Output RF Modules:	Hot Swappable

Physical:	
Dimensions:	1 RU (1.75" H x 19" W x 18.5" D)
Weight:	14 lbs.gross (boxed), 11.2 lbs. net
Certifications:	CE, TUV NRTL, FCC Part 15

Environmental Parameters:	
Operating Temperature:	0 to 50° C
Storage Temperature:	-10° C to 75°C
Humidity:	20 % to 90% non-condensing
Altitude:	10,000 feet AMSL

250 Airport Road • Indiana, PA 15701 • (800) 839-3658 • (724) 349-1412 • Fax: (724) 349-1421

<http://www.quintechelectronics.com/> • info@quintechelectronics.com

© 2023 Quintech Electronics and Communications Inc. All rights reserved. All product designs and specifications are subject to change without notice
QF12200V16X16CS3AA1000 Rev J, CO# 32249 (Page 2 of 2)