

XTREME 32-C

32 Port Fan-In RF Matrix Switch

QF13500V16X16CS3AA1000

16x16 SMA(f)

Exclusive Flexible Matrix Architecture, Industry Leading Specifications, and Hot-Swappable Components Provide an XTREME Signal Management Solution

The **XTREME 32** Dual Band matrix switch is a full fan-in (combining) non-blocking signal management solution that routes an input to any or all outputs. The design features an industry exclusive architecture that supports both symmetric and asymmetric configurations of 32 combined inputs and outputs in a compact 1 RU chassis. Hot-Swappable redundant power supplies, I/O Modules, and a field replaceable cooling fan provide maximum reliability.

950-3500 MHz Operating Range

Flexible Matrix Configurations (16x16)

Redundant Hot Swappable Power Supplies

Hot-swappable Input and Output Adapters

Adjustable Input and Output Gain

Dual Gigabit Ethernet Ports

Field Replaceable Cooling Fan



Convenient Local Control and Status Monitoring

Field Replaceable Cooling Fan

Hot Swappable I/O Adapters

Independent Input and Output gain control to balance levels and cable loss

Dual Gigabit Ethernet Ports Remotely controllable via secure web browser interface, SNMP, TCP, API, or TELNET



SMA, BNC 50, BNC 75, and mixed connector configurations available.

Hot-swap Redundant Power Supplies

250 Airport Road • Indiana, PA 15701 • (800) 839-3658 • (724) 349-1412 • Fax: (724) 349-1421

<http://www.quintechelectronics.com/> • info@quintechelectronics.com

© 2023 Quintech Electronics and Communications Inc. All rights reserved. All product designs and specifications are subject to change without notice
QF13500V16X16CS3AA1000 Rev D, CO# 32249 (Page 1 of 2)

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
ISO 9001

QUINTECH
The Source for RF Reliability



32 Port Fan-In RF Matrix Switch

Specifications and Operating Conditions

As Configured/Expandable to:	16x16	
RF Connectors:	SMA(f)	
Operating Frequency:	950-3500 MHz	
	950-2150 MHz	950-3500 MHz
Frequency Response: Default Gain: typically Centered @ 0 dB	+/- 2.0 dB	
Any 36 MHz:	+/- .5 dB	+/- .5 dB
Input P1dB:		
Default Gain:	0 dBm min	
Max Input Gain:	-10 dBm typical *	
Noise Figure:		
Default Gain:	13 dB max (22 dB Full Fan-In)	15 dB max (24 dB Full Fan-In)
Max Input Gain:	9 dB typical * (21 dB typical Full Fan-In)	10 dB typical * (23 dB typical Full Fan-In)
OIP3:		
Default Gain:	10 dBm min	8 dBm min
Input Return Loss:	14 dB min	14 dB min
Output Return Loss:	14 dB min	14 dB min
Isolation:		
Input to Input:	50 dB min	
Output to Output:	50 dB min	
Input to Output:	50 dB min	45 dB min
Input Gain Range:	-19.5 to 12 dB in .5 dB steps	
Output Gain Range:	-20.5 to 11 dB in .5 dB steps	
RF Sensing Range:	-50 to 0 dBm	
AGC Tracking Range:	-50 to -10 dBm setpoint	
Switching Speed:	150 mS per crosspoint typical *	
	<2 uS from break to make	
Maximum Input Power: (No Damage)	20 dBm (30 VDC max on any port)	

Control:	
Local Control:	
Front Panel 2.2" LCD Display with Rotary Knob	
Remote Control:	
Dual 10/100/1000 Base Tx Ethernet Ports	
SNMP	v2c, v3
TCP/IP	Quintech 2.15 Protocol (Port 9100)
Web Server	
Secure Web Server with Custom SSL Certificate	
TELNET with option to disable	
Macro Scripting Language to Automate Changes and Monitoring	
XR Bus Expansion Standard	
Optional Ethernet Expansion	
NTP Time Client	

Alarms and Logging:	
SNMP Traps on Status Change	
SNMP Trap on Crosspoint Change	
SysLog, SQL, or CSV Format Log File	
Q-Sense:	
Primary and Backup Input Pairs: Backup is automatically switched if the Primary Input falls below the threshold level.	

Power and Cooling Requirements:	
AC Input Range:	100-240 VAC Autoranging 50/60 Hz 5A
Hot-Swappable Redundant Supplies with Separate AC Inlets	
Power Consumption:	100 W typical
Fan:	Long-life ball bearing fan (field)
Input and Output RF Modules:	Hot Swappable

Physical:	
Dimensions:	1 RU (1.75" H x 19" W x 18.5" D)
Weight:	14 lbs. gross (boxed), 11.2 lbs. net
Certifications:	CE, TUV NRTL, FCC Part 15

Environmental Parameters:	
Operating Temperature:	0 to 50° C
Storage Temperature:	-10° C to 75°C
Humidity:	20 % to 90% non-condensing
Altitude:	10,000 feet AMSL

* typical refers to expected product performance that is useful in application of the product but is not covered by the product warranty

250 Airport Road • Indiana, PA 15701 • (800) 839-3658 • (724) 349-1412 • Fax: (724) 349-1421

<http://www.quintechelectronics.com/> • info@quintechelectronics.com

© 2023 Quintech Electronics and Communications Inc. All rights reserved. All product designs and specifications are subject to change without notice
QX13500V16X16CS3AA1000 Rev D, CO# 32249 (Page 2 of 2)